

3 PATTERN LIGHT SERIES INSTRUCTIONS

Applicable to all 200A, 200C, 200Z, 201B, 201Z, 201ZB, 204R, 208R, 200xx, 27xxx, 16xxx, 24xxx series lights

Caution:

- Do not at any point touch the LEDs.
- DO NOT TEST OR OPERATE any light using a battery charger. This will destroy the microprocessor and void warranty.

Wiring

- All extension wires should be the same gauge as those coming from the light. Please see the table below for the recommended wire gauge.

<u>Wire Colour</u>	<u>Wire Gauge</u>	<u>Wire Function</u>
Red	18AWG	Positive (+)
Black	18AWG	Negative/Ground (-)
Green	22AWG	Pattern Select

Quick Wiring Table

<u>Function</u>	<u>Green Wire</u>
Double Flash	Hold to Negative (-)
Single or Triple Flash (depends on model)	No Connection
Quad Flash	Hold to Positive (+)

Operation

- It you have a model with the Green wire connected to a 3-position switch, the flash patterns can be cycled through by switching between the different positions.
- If you wish to have only one (1) pattern, connect the green wire permanently as in the table above.

Trouble Shooting

If your light fails to work, please follow these troubleshooting techniques before calling the factory:

- Check all connections for breakage or corrosion
- Check to see if the fuse has blown. If it has, replace with a fuse of the exact same amp rating.
- Ensure vehicle's battery is charged and that the charging system is functional.

CALL SWS CANADA (1-877-357-0222) FOR FURTHER PRODUCT ASSISTANCE



SWS - WARNING SYSTEMS INC.

7695 Blackburn Pkwy • Niagara Falls • Ontario • L2H 0A6 • Canada
Phone: 905.357.0222 • Toll Free: 1.877.357.0222 • Fax: 905.357.9122
Web: www.SWSCanada.com

*We Manufacture and
Service What We Sell !*

300102_Rev5